

Vistex

ST-221U

BRIEF DESCRIPTION

- New woven fabric textured white surface and rough grey back, both sides with PA coating
- Easy operate as wall covering with glue
- Good flatness and perfect opacity, ideal choice for roll up, frame, etc
- Max 5m width makes it more widely used

FEATURES



PVC-FREE



PHTHALATE FREE



FULL OPACITY



5m
SUPER WIDE

INK PRINTABILITY



UV



LATEX

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	300 g/sq.m	8.8 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Woven	
Shielding Rate	ANSI PH2.19, ISO 5/2	99%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.